

FE-SPK-IP1

FE-SPK-IP1 is an active PoE+ SIP-speaker able to connect to any SIP-server as standard SIP-client and get a phone call as standard SIP-extension.

Simple installation and setup, Vandal-proof.

Audio files and voice messages can be streamed live or uploaded to device to play them later or periodically from built-in timer/scheduler. Auto-provisioning through IP-INTEGRA SIP-server saves time, especially in the case of large-scale installations. The module can easily be integrated with 3rd party SIP systems through WEB interface.



At a first glance

- EN 54-24 Certification, BS 5839 Part 8 and EN 60849 Compliant
- Vandal-proof
- User-friendly WEB interface for Remote Setup
- Fitted with a 5" Twin Cone Driver Unit
- Designed for wide response (music and speech)
- Self-diagnosing and reporting through e-mail
- 10W Additional Output for connecting an extra Passive Speaker



Specification

HARDWARE

Ethernet connector 1x RJ 45

Power Options PoE and/or external PS 5V/1.5A DC

PoE IEEE 802.3at

Power Consumption Idle: 1.8W / Max: 20W (Volume dependant) CPU Allwinner H2+, Quad-core Cortex A-7

NETWORKING AND PROTOCOLS

Protocols IPv4 (with DiffServ), SIP, TCP, UDP, HTTP, RTP, DHCP, SNMP, NTP

LAN Protocols PoE (802.3at) Network Access Control (802.1x)

HTTP (Web Configuration) DHCP and Static IP, Remote Software upgrade, Centralized Management and operation

monitoring

RFC3261 (SIP Base Standard), RFC3515 (SIP Refer), RFC2976 (SIP Info), SIP using SIP Support

TLS, RFC5630 SIPS Uri scheme

DTMF Support RFC2833, 2976 (SIP Info)

OTHER SPECIFICATIONS

1x I/O PIN Input

5V DC and 12V DC Output

3x Open-Controller @ 2A, up to 15V (LED RGB Button drive)

Microphone 1 On-board connector

SPEAKER SPECIFICATION

Rated Power 6 W Ω 8 Impedance 90 dB SPL (1W/1m) MAX SPL (Rated W/1m) 98 dB

Frequency range (-10dB) 190 Hz to 18 kHz Dispersion 1 kHz / 4 kHz 175° / 65° Operating temperature -30°C to +60°C

Power Selection PoE+

Material Housing: Steel

Colour and finish White

Dimensions 163.5x163.5x60 mm (HxWxD)

Net Weight 2kg Mounting Screws



Freund Elektronik A/S, in cooperation with our sister company Freund Elektronika D.O.O. Sarajevo, is developing an IP-Based Intercoms, Audio Systems, Access Control and Smart Home solutions.

As a developer, manufacturer, and reseller, we have been self-improving and perfecting ourselves for over 30 years.

In the industry, we negotiate the most advanced and innovative solutions regarding the building communication. Our daily focus is on the development and user friendliness of our high quality and pleasantly designed products.

As a developer and manufacturer of our own IP-INTEGRA system, we have made a top-of-the-line products for Door Telephony, Public Audio, and Access Control solution.

Our development department, together with our partners, has created elegant and robust door phones, SIP-Centrals, Terminals, IP-Speakers, ACC Controllers, and applications with intelligent features using the most advanced technologies when available, and creating new technologies when they are not while keeping it simple for our customers.